

The Navigator, and the Expedition require only one programmed transponder as well as the "to be added" transponder.

- 1 Turn the ignition key on for two seconds, then off with a programmed key.
- 2 Within 10 seconds, Start the vehicle using the remote start unit having the "to be added" transponder within range of the exciter coil. After two seconds, the theft indicator will turn off indicating that the new transponder has been learned.

Note when using the AS-TBM module, or any other transponder by pass circuit, you should installed it prior to the above procedure.

NOTE Because of the timed start sequence in the APS-750 and the PRO-9671 there may be some confusion when you get to step 3 for the two transponder vehicles, or step two for the one transponder vehicles.

Ten seconds after the ignition is turned off, the remote start unit is capable of entering the timed start mode.

If the transmitter is operated 4 times within 10 seconds of the ignition switch being turned off, the siren will emit 4 chirps indicating that the unit entered timed start mode. Waiting for the chirp cycle to complete, and then double pushing two times to start the vehicle, will allow too much time to pass and you will exit the vehicle's 10 second transponder learn cycle.

During step two or three above you must press the transmitter start button six times. This will cause the remote start unit to bypass the timed start mode and immediately enter the start cycle. This can be achieved within 5 seconds of turning off the key, leaving plenty of time to learn the added transponder.

DO NOT WAIT FOR THE TIME START CHIRPS TO COMPLETE, SIMPLY PRESS THE TRANSMITTER 6 TIMES IN SUCCESSION TO BYPASS THE TIME START MODE, IMMEDIATELY REMOTE STARTING THE VEHICLE.

Programming additional transponders in the 98 Ford products for use with remote start units.

Vehicles involved: Navigator, Expedition, Mustang, Taurus, Sable, Grand Marquis, Crown Victoria, Mountaineer, and Explorer.

The procedure for programming additional transponders in the listed 98 vehicles has changed and will effect the way in which, when coupled with a remote start unit, you program your additional transponder.

To program a additional transponders in the Mountaineer, Mustang, Taurus, Sable, Grand Marquis, Crown Victoria, and Explorer you require two programmed transponders as well as the "to be added" transponder.

- 1 Turn the ignition key for two seconds, on then off with a programmed key.
- 2 Within 5 seconds, turn the ignition key on for two seconds, then off with the second programmed key.
- 3 Within 10 seconds, Start the vehicle using the remote start unit having the "to be added" transponder within range of the exciter coil. After two seconds, the theft indicator will turn off indicating that the new transponder has been learned.