

K-9 Classic

REMOTES: 2 - 143-01 Pictogram Remotes with Glow Buttons. Board # ETOC

REMOTE OPERATION:

LOCK- Press and release to arm/lock system. Press and hold to activate panic with locking doors.

UNLOCK- Press and release to disarm/unlock system. Press a second time within 5 seconds to activate the 2nd unlock output. Press and hold to activate panic with unlocking doors.

II- Press and hold for 2 seconds to activate the 2nd channel output. Press and release twice to arm/lock or disarm/unlock without chirps.

III- Press and hold for 3 seconds to activate 3rd channel output.

CODING REMOTES: Turn the ignition “ON”. Press and release valet button 5 times. Wait for audible response. Press Lock Button on each remote to be coded. (One at a time.)

ZONE VIOLATION CODE: After remotely disarming the LED will flash one of the following codes if the alarm was activated while it was in an armed state.

Flash 2X- System was activated from the hood or trunk circuit wire.

Flash 3X- System was activated from the door circuit wire.

Flash 4X- System was activated from the auxiliary input.

NOTES

- 1) Unit uses a 5 and 8 pin harness
- 2) Unit has one 4 pin auxiliary port..
- 3) Unit has 4 pin door lock port.
- 4) Unit has onboard relay for dome light supervision.
- 5) Unit has LED-SP micro plug for LED.
- 6) Unit has back up battery plug.
- 7) Unit has data port for FPM-1 programmer.
- 8) 3rd channel output is in pin 1 of 8 pin harness.
- 9) Unit has Smart Trigger.
- 10) Unit has enhanced panic.

PROGRAMMABLE FEATURES

Turn ignition on then off. Press valet button 5 times. Wait for siren response. Press valet button 1 time. Wait for response. Press valet button equal to the number of the feature you wish to change. Large button turns feature on small middle turns feature off.

FEATURE#	DEFAULT	LOCK	II
Feature #1 Ignition Activated Anti-Carjacking Protection	OFF	ON	OFF
Feature #2 Door Activated Anti-Carjacking Protection	OFF	ON	OFF
Feature #3 Last Door Arming	ON	ON	OFF
Feature #4 Doors Lock with Last Door Arming	ON	ON	OFF
Feature #5 Current Sensing	ON	ON	OFF
Feature #6 Doors Lock With Ignition “ON”	ON	ON	OFF
Feature #7 Ignition OFF Unlock #1	ON	ON	OFF
Feature #8 Ignition OFF Unlock #2	OFF	ON	OFF
Feature #9 Open Door Bypass To The Previous Three Features	ON	ON	OFF
Feature #10 Lights On 5/30 Seconds Upon Disarm	30 sec.	30 sec.	5 sec.
Feature #11 Automatic Rearming	ON	ON	OFF
Feature #12 Disarm Upon Activating 2 nd Channel	ON	ON	OFF
Feature #13 Door Lock Pulse Time	.8 sec.	.8 sec.	3 sec.
Feature #14 Double Pulse Unlock	OFF	ON	OFF
Feature #15 Arming Delay	3 sec.	3 sec.	45 sec.
Feature #16 Confirmation Chirps	ON	ON	OFF
Feature #17 Activated Alarm Cycle	60 sec.	60 sec.	30 sec.
Feature #18 Pulsed Horn / Steady Siren Output	Steady	Steady	Pulsed
Feature #19 Loud or Soft Pulsed Horn Chirps	Loud	Loud	Soft
Feature #20 Total Closure Lock Output	OFF	ON	OFF
Feature #21 Transmitter Activated Anti-Carjacking Protection	OFF	ON	OFF
Feature #22 One / Two Button Arming / Disarming	TWO	TWO	ONE

TOTAL SYSTEM RESET

Must use FPM-1 or be returned to factory.

K-9 Classic Wiring Overview

